

Cascada Showers – Product Technical Specification Sheet

Model: Savona – Dual-Function 2-Handle Thermostatic Valve (CSK02YM)

Product Overview

The Cascada Savona Thermostatic Valve offers precise temperature control and dual-function flow management through two independent outlets. Designed with durability and safety in mind, it's ideal for modern bathrooms requiring both elegance and functionality.

Technical Specifications

Specification	Details
Valve Function	Dual outputs controlled by two ergonomic
	handles
Inlet Connections	2 inlets; ½" female NPT (hot & cold)
Outlet Connections	2 outlets; ½" female NPT
Maximum Water Pressure	120 PSI
Rough-In Depth	$2 \frac{3}{4}$ " – 4 " (70–100 mm) from the finished
	wall surface to the back of the valve
	housing
Installation Method	Wall-mounted rough-in valve with
	integrated flush box and cover
Housing Features	Leak-proof casing with built-in protective
	cover
Materials & Build	Lead-free brass body; trim plate in multiple
	premium finishes
Available Finishes	Chrome, Brushed Nickel, Matte Black,
	Brushed Gold, etc.
Certification	cUPC certified; compliant with Uniform
	Plumbing Code
Warranty	5-Year Limited Warranty

Key Features & Benefits

- Precise thermostatic control with anti-scald safety.
- • Independent control of two water outlets (e.g., showerhead and hand shower).
- Solid brass body ensures corrosion resistance and long life.
- Easy installation with pre-mounted flush box and serviceable components.
- Compatible with standard US plumbing systems.

Recommended Applications

Perfect for upscale residential bathrooms, guest suites, and commercial hospitality settings where dual-function water control and modern aesthetics are desired.

Installation & Maintenance Notes

The Savona valve is compatible with standard ½" NPT plumbing systems. No special tools are needed for trim installation. In areas with hard water, it is recommended to inspect and clean the valve cartridge periodically to ensure optimal performance.